



HICKS oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Universal CVT Fluid

Venom[®] Universal Continuously Variable Transmission (CVT) Fluid is a premium full synthetic transmission fluid specifically designed to be suitable for use in virtually all belt-type continuously variable transmissions. With this approach, this fluid has the ability to provide quality lubrication while simplifying inventories and reducing the chance of using an incorrect fluid.

Venom[®] Universal CVT fluid is suitable for use in the following types of CVTs:

- Toyota (TC)
- Honda HMMF (recommended 20,000 miles drain intervals)
- Nissan (NS-III)
- Mitsubishi (SP-III)
- Subaru (NS-2)
- Daihatsu (TC)
- Hyundai/Kia (SP-III)
- Dodge Caliber (NS-II)
- Ford (CVT23)
- GM/Saturn (DEX-CVT)
- CVTF-J1

Venom[®] Universal Continuously Variable Transmission is not recommended for CVTs produced by VW/Audi, and has a recommended 20,000 mile drain interval for the Honda CVT.

Typical Properties:

Product: Venom [®] Universal CVT Fluid	
Product Code	90273
Color	Red
Kinematic Viscosity @ 100 °C, cSt (ASTM D-445)	7.1
Brookfield Viscosity @ -40°C, cP (ASTM D-2983)	11,800