



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Synthetic M/D III Automatic Transmission Fluid

Venom® Synthetic Automatic Transmission Fluid M/D III is formulated from premium API group III synthetic base oils blended with a specially balanced additive combination to meet the requirements of Mercon and Dexron III automatic transmissions. This product has outstanding high temperature oxidation resistance, dispersancy and detergency; offers excellent protection against corrosion, wear and rust; and is compatible with the various automatic transmission components such as elastomeric seals and plastic parts. In addition, its high viscosity index permits use over a wide temperature range by providing excellent low temperature fluidity and at the same time retaining the desired viscosity at high temperatures. It contains special friction modifiers that provide the smooth lock-ups required by the ATF specifications.

Venom® Synthetic Automatic Transmission Fluid M/D III is recommended for use in many types of automatic transmissions. This generally includes all automatic transmissions except those which specify Ford M2C33-F (Type F) fluids. It may also be used in Allison automatic transmissions, including those that require C-4 fluids, and Caterpillar transmissions requiring TO-2 performance. It satisfies Ford specifications M2C138-CJ and M2C166-H.

Always follow manufacturer's recommendations for fluid type

Typical Properties:

Product: Venom Synthetic M/D III Automatic Transmission Fluid	
Product Code	1351
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	7.0
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	36.0
Viscosity Index (ASTM D-2270)	180
API Gravity (ASTM D-1298)	33.0