



HICKS oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Synthetic CJ-4 /SN 15W-40 Motor Oil

Venom[®] Synthetic CJ-4/SN 15W-40 Motor Oil is for use in diesel engines under service conditions from mild to heavy duty with fuel of any sulfur level. This oil is recommended for use in nearly all two- and four-cycle diesel applications. The current formulation meets or exceeds all API Service Classifications up to CJ-4 including CI-4, CI-4 PLUS, and CH-4. Venom[®] Synthetic CJ-4/SN 15W-40 is also suitable where Cummins CES 20081, Mack EO-O Premium Plus, Detroit Diesel DDC 93K218, Volvo VDS-4, Renault VI RLD-3, CAT[®] ECF-3 and ECF-1-a, and ACEA E7 and E9 specifications are demanded.

Utilizing premium performance additives in synthetic base oils, this full synthetic motor oil offers outstanding protection from engine wear, sludge formation, deposit build up, and thermal oxidative degradation. These characteristics make Venom[®] Synthetic CJ-4/SN 15W-40 Motor Oil an excellent choice for driving under severe conditions such as excessive stop and go driving, extremes in temperature, or heavily loaded hauling and towing.

This oil should not be used in Caterpillar TO-4 applications, two-cycle gasoline engines, aircraft engines, or EMD Diesel engines.

Typical Properties:

Product: Venom [®] CJ-4/SN 15W-40	
Product Code:	61169
SAE Viscosity Grade	15W-40
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	15.66
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	114.4
Viscosity Index (ASTM D-2270)	145
Total Base Number (ASTM D-2896)	9.2
Zn (ppm)	1100
Ca (ppm)	2300
P (ppm)	1000
Pour Point, °C (ASTM D5949)	-39