



HICKS oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431



## GL-4, GL-5 Multi-Purpose Gear Oils

Nature's Choice® Multi-Purpose Gear Oils are used for the lubrication of gears operating under severe conditions, including automotive applications. High quality HVI base stocks blended with a sulfur-phosphorous extreme pressure additive package provide superior performance including anti-weld, anti-scuff, and anti-wear properties.

Nature's Choice® Multi-Purpose Gear Oils are available in API GL-4 and GL-5 performance levels. The GL-4 level is designed for spiral-bevel and hypoid gears under moderate speeds and loads. This level is recommended for some manual transmissions and transaxles.

Nature's Choice® GL-5 Multi-Purpose Gear Oils have multi-grade characteristics and are recommended for hypoid gears in moderate and severe service, including shock-loading, and some manual transmissions. GL-5 Gear Oils also meet or exceed the MIL-L-2105D specification, API MT-1 for truck manual transmissions, Meritor O76-D/A, MAN 342 Type M1/M2, Mack GO-J, and SAE J2360.

The Nature's Choice® product line was developed in response to President Clinton's Executive Order 13101 which mandated the use of motor oils with re-refined content for government use. Since that time, the Nature's Choice® product line has grown from motor oils to include many other types of lubrication. Blending virgin and re-refined base stocks with quality additive chemistry, Nature's Choice® brand products are able to meet the top performance grades required for today's lubrication requirements, while being more environmentally friendly.

Nature's Choice® GL-4, GL-5 Multi-Purpose Gear Oils are not intended for use in automotive gear boxes that require a limited slip gear oil. Always follow manufacturers' recommendations for correct type and viscosity grade of gear lubricant.

### Typical Properties:

Product: Nature's Choice® GL-4 and GL-5 Gear oils				
Product Code	101421	101422	101411	101412
API Classification	GL-4	GL-4	GL-5	GL-5
SAE Viscosity Grade	90	140	80W-90	85W-140
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	14.8	30.2	15.6	27.2
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	149.5	415.0	160.7	378.1
Viscosity Index (ASTM D-2270)	98	98	99	97
API Gravity (ASTM D-1298)	28.3	28.0	28.2	26.3
Pour Point, °C (ASTM D-5949)	-30	No Data	-33	-21