



Safety Data Sheet

Issuing Date 22-Jan-2009

Revision Date 21-May-2014

Version 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Synthetic Blend CJ-4/SM 15W-40 Motor Oil

Other means of identification

Product Code(s) 61179

Synonyms No information available

Recommended use of the chemical and restrictions on use

Recommended Use Engine oil, Lubricant.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Hicks Oils
845 N. Hickory Street
Du Quoin, IL 62832
TEL: 618-542-5431

Emergency telephone number

Company Phone Number 618-542-5431

Company Emergency Phone Number (618) 542-5431

Emergency telephone number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1

Label elements

EMERGENCY OVERVIEW

WARNING

Hazard statements

Causes serious eye irritation

May cause an allergic skin reaction



Appearance Amber colored liquid

Physical state viscous liquid

Odor Mild petroleum odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

Specific treatment (see supplemental first aid instruction on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- MAY BE HARMFUL IF SWALLOWED
- May be harmful in contact with skin
- Causes mild skin irritation
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown Aquatic Toxicity

0.83% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Common Name Hydrocarbon Lubricating Fluid.
Chemical Family Synthetic Hydrocarbon, Petroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	78	*
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	84605-29-8	0.85-1.68	*
Benzenesulfonic Acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	0.17-0.83	*
Phenol, dodecyl-, branched	121158-58-5	0.02-0.15	*
2,6-di-tert-butylphenol	128-39-2	0.02-0.15	*
Toluene	108-88-3	0.002	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice No hazards which require special first aid measures.

Eye contact Flush eyes for 30 minutes with water. Get medical attention if irritation persists.

Skin contact Wash off immediately with soap and plenty of water.

Inhalation Move exposed persons to fresh air. Consult medical personal if breathing issues occur.

Ingestion Do NOT induce vomiting. Consult a physician.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Carbon dioxide (CO₂). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

Small Fires Always use personal safety equipment. Follow appropriate personal safety procedures, and extinguishing media.

Large Fires Contact emergency personnel.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Combustible material.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal protection Avoid contact with the skin and the eyes. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as material can cause surfaces to become very slippery.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Cover with earth, sand, or other non-combustible material followed with plastic sheets to minimize spreading or contact with rain.

Methods for cleaning up Excess liquid material can be collected using a scoop or shovel and stored for recycling or disposal. Prevent material from entering drains or waterways.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at ambient temperature.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat and sources of ignition. Keep containers closed when not in use. Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidelines for storage of material for amount stored.

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines This product contains the following hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face Protection If splashes are likely to occur, wear: Goggles. Eye/face Protection.

Skin and body protection Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin wash with soap and water.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	viscous liquid	Odor	Mild petroleum odor
Appearance	Amber colored liquid	Odor threshold	No information available
Color	amber	Remarks • Method	
Property	Values		
pH	No information available		
Melting point/freezing point	No information available		
Boiling Point/Range	No information available		
Flash point	> 93.3 °C / > 200 °F		Cleveland open cup (COC)

Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific gravity	0.88
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	
Decomposition temperature	No information available
Kinematic viscosity	14.4 @100C mm ² /s
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other information

Softening point	No information available
VOC Content	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	------------------------------------------

Conditions to avoid

Excessive heat. High energy sources of ignition.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	Inhalation of vapors in high concentration may cause irritation of respiratory system.
Eye contact	Avoid contact with eyes. May cause irritation.
Skin contact	May cause eye/skin irritation. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Do NOT taste or swallow.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	= 2000 mg/kg (Rat)	> 3200 mg/kg (Rabbit)	-
Phenol, dodecyl-, branched 121158-58-5	= 2100 mg/kg (Rat)	= 5 mL/kg (Rabbit)	-
2,6-di-tert-butylphenol 128-39-2	> 5000 mg/kg (Rat)	> 10 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation Irritating to eyes.
Sensitization May cause sensitization by skin contact.
Germ cell mutagenicity No information available.
Carcinogenicity No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	Group 1	-	X
Toluene 108-88-3	-	Group 3	-	-

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.
Developmental toxicity Contains ingredients that have suspected developmental hazards.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard Not Applicable.

Numerical measures of toxicity - Product Information

Unknown Aquatic Toxicity 0.83% of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION**Ecotoxicity**

1.66% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	-	10 - 100: 96 h Pimephales promelas mg/L LC50 static 38: 96 h Pimephales promelas mg/L LC50 100: 96 h Pimephales promelas mg/L LC50 semi-static	0.1 - 1: 48 h Daphnia magna mg/L EC50
Phenol, dodecyl-, branched 121158-58-5	-	0.14: 96 h Oncorhynchus clarki mg/L LC50	-
2,6-di-tert-butylphenol 128-39-2	-	-	0.45: 48 h Daphnia magna mg/L EC50

<p>Toluene 108-88-3</p>	<p>433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static</p>	<p>15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static</p>	<p>5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50</p>
-----------------------------	------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
<p>Toluene 108-88-3</p>	<p>2.65</p>

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Method

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
<p>Toluene 108-88-3</p>	<p>waste number U220</p>	<p>Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151</p>	<p>-</p>	<p>-</p>

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
<p>Toluene 108-88-3</p>	<p>-</p>	<p>-</p>	<p>Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.</p>	<p>-</p>

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Toluene 108-88-3	Toxic; Ignitable

14. TRANSPORT INFORMATION

DOT Not regulated

IATA PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO TI OR IATA DGR

15. REGULATORY INFORMATION

International Inventories

TSCA	Does not comply
DSL/NDSL	Does not comply
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Does not comply
KECL	Does not comply
PICCS	Does not comply
AICS	Does not comply

Legend:

All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
---------------	-----------------------------	------------------------	---------------------------	----------------------------

Toluene 108-88-3	1000 lb	X	X	X
---------------------	---------	---	---	---

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Prop. 65
Toluene - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	X	-	X
Toluene 108-88-3	X	X	X

U.S. EPA Label Information

EPA Pesticide registration number Not Applicable

16. OTHER INFORMATION

NFPA	Health hazards 1	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection X

Issuing Date 22-Jan-2009

Revision Date 21-May-2014

Revision Note

(M)SDS sections updated 2 3 5 7 8 9 10 11 13 14 15 16

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS