



Hicks Oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431

# FORMULA 500

## Universal Continuously Variable Transmission Fluid

**Formula 500®** Universal Continuously Variable Transmission (CVT) Fluid is a premium full synthetic transmission fluid specifically designed to be suitable for use in virtually all belt type continuously variable transmissions. With this approach, this fluid has the ability to provide a quality product while simplifying inventories and reducing the chance of using an incorrect fluid.

**Formula 500®** Universal Continuously Variable Transmission fluid is suitable for use in the following types of CVTs:

- Toyota (TC)
- Honda HMMF (recommended 20,000 miles drain intervals)
- Nissan (NS-II)
- Mitsubishi (SP-III)
- Subaru (NS-2)
- Daihatsu (TC)
- Hyundai/Kia (SP-III)
- Dodge Caliber (NS-II)
- Ford (CVT23)
- GM/Saturn (DEX-CVT)
- CVTF-J1

**Formula 500®** Universal Continuously Variable Transmission is not recommended for CVTs produced by VW/Audi, and has a recommended 20,000 mile drain interval for the Honda CVT.

### Typical Properties:

Product: Formula 500 Universal CVT Fluid	
Product Code	90273
Color	Red
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	7.1
Brookfield Viscosity @-40C (ASTM D-2983)	11,800 cP