



HICKS oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



ANTI-WEAR HYDRAULIC OILS

FORMULA 500® Anti-Wear (AW) Hydraulic Oils are superior anti-wear hydraulic and circulating fluids specially formulated with high quality base stocks and improved thermally stable zinc additives. These oils offer outstanding resistance to sludge formation, are chemically stable, and exhibit excellent anti-wear properties. FORMULA 500® AW Hydraulic Oils also contain anti-foam agents to limit air entrainment in hydraulic systems, and demulsifiers to separate water from the oil in the sump.

FORMULA 500® AW Hydraulic Oils are recommended for service in vane, piston, and gear pumps when used according to the manufacturers' recommendations. The oils provide maximum service life to these pumps as well as other system components. FORMULA 500® AW Hydraulic Oils ISO 10 and ISO 22 products can also be used as spindle lubricants.

FORMULA 500® AW Hydraulic Oils meet the following specifications:

- Denison HF-0, 1, and 2
- Vickers M-2950-S, I-286-S
- Cincinnati Milacron P-68, 69, 70
- US Steel 126, 127, and 136
- DIN 51524 Part 2

Typical Properties:

Product: FORMULA 500® Anti-Wear Hydraulic Oils							
ISO Viscosity	10	22	32	46	68	100	150
Product Code	90418	1211	1212	1213	1214	1215	1216
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	2.76	4.6	5.7	7.1	9.1	11.40	15.00
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	11.20	23.2	32.1	45.1	66.4	100.00	150.00
Viscosity Index (ASTM D-2270)	77	117	119	115	112	100	100
RPVOT, min (ASTM D-2272)	(no data)	300	300	300	300	200	200
Emulsion Separation, min (ASTM D-1401)	(no data)	10	10	15	15	15*	15*
Pour Point, °C (ASTM D-5949)	(no data)	-36	-39	-30	-30	-12	-12
Flash Point, °F (ASTM D-92)	(no data)	(no data)	435	446	470	(no data)	(no data)