



HICKS oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



API SN Conventional Motor Oils

FORMULA 500[®] API Service SN Conventional Motor Oils are designed to meet the high performance requirements initiated in 2011 automotive lines. FORMULA 500[®] API SN Conventional Motor Oils use high quality petroleum base stocks along with state of the art additive technology to create a high quality motor oil for use in gasoline powered engines. FORMULA 500[®] API Service SN Conventional Motor Oils provide excellent protection against wear and deposits in the engine, while extending the life of emission control components. This premium blend of motor oil allows up to 5,000 miles between oil changes.

FORMULA 500[®] API Service SN Conventional Motor Oils formally carry the American Petroleum Institute's (API) SN approvals, and the 5W-20, 5W-30, and 10W-30 viscosities are Resource Conserving and are ILSAC GF-5 approved. The API donut and ILSAC starburst identify oils which have undergone the necessary testing to meet the current automotive specification. These oils are fully backwards compatible to all older API gasoline powered engine specifications such as SM, SL, SJ, etc.

Always follow manufacturer's recommendations for service classification, viscosity grade and drain intervals.

Typical Properties:

Product: FORMULA 500 [®] SN Conventional Motor Oils						
SAE Viscosity Grade	30	5W-20	5W-30	10W-30	10W-40	20W-50
API Classification, (ILSAC Classification)	SN	SN (GF-5)	SN (GF-5)	SN (GF-5)	SN	SN
Product Code	51123	51125	51126	51127	51128	51120
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	11.0	8.6	10.9	9.9	15.7	17.9
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	90.1	49.7	64.9	64.1	107.4	147.4
Viscosity Index (ASTM D-2270)	107	151	160	139	153	134
Total Base Number (ASTM D-2896)	7.2	7.2	7.2	7.2	7.2	7.2
API Gravity (ASTM D-1298)	29.3	33.0	33.0	31.7	32.2	29.2
Zn (ppm)	850	850	850	850	850	850
Ca (ppm)	2100	2100	2100	2100	2100	2100