



# Safety Data Sheet

Issuing Date 15-Feb-2010

Revision Date 03-Mar-2017

Version 3

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product name** All Weather AW Hydraulic Fluids; ISO 22, 32, 46

### Other means of identification

**Product Code(s)** 11211, 11212, 11213  
**Synonyms** No information available

### Recommended use of the chemical and restrictions on use

**Recommended Use** Hydraulic Fluid, Lubricant.  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Hicks Oils  
845 N. Hickory Street  
Du Quoin, IL 62832  
TEL: 1-618-542-5431

#### **Emergency telephone number**

**Company Phone Number** 618-542-5431  
**Company Emergency Phone Number** (618) 542-5431  
**Emergency telephone number** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

### Label elements

#### EMERGENCY OVERVIEW

**Appearance** Transparent, yellow tinted fluid  
**Physical state** -  
**Odor** Mild petroleum odor

### Hazards not otherwise classified (HNOC)

#### **Other information**

Unknown Aquatic Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Common Name** Hydrocarbon Lubricating Fluid.  
**Chemical Family** Petroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
---------------	--------	----------	--------------

Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	42-80	*
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	10-43	*
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0-14.3	*
2-ethylhexyl zinc dithiophosphate	4259-15-8	0.24-0.36	*
2,6-di-tert-butylphenol	128-39-2	0.03-0.06	*
calcium alkylarylsulphonate	90194-27-7	0.01-0.03	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### First aid measures

<b>General advice</b>	No hazards which require special first aid measures.
<b>Eye contact</b>	Flush eyes for 30 minutes with water. Get medical attention if irritation persists.
<b>Skin contact</b>	Remove contaminated shoes and clothing and cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops and persists, seek medical attention.
<b>Inhalation</b>	Move exposed persons to fresh air. Consult medical personnel if breathing issues occur.
<b>Ingestion</b>	Do NOT induce vomiting. Consult a physician.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

##### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

**Small Fires** Always use personal safety equipment. Follow appropriate personal safety procedures, and extinguishing media.

**Large Fires** Contact emergency personnel.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

Combustible material.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal protection** Avoid contact with the skin and the eyes. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as material can cause surfaces to become very slippery.

#### Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

#### Methods and material for containment and cleaning up

**Methods for containment** Cover with earth, sand, or other non-combustible material followed with plastic sheets to minimize spreading or contact with rain.

**Methods for cleaning up** Excess liquid material can be collected using a scoop or shovel and stored for recycling or disposal. Prevent material from entering drains or waterways.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Advice on safe handling** Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at ambient temperature.

#### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat and sources of ignition. Keep containers closed when not in use. Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidelines for storage of material for amount stored.

**Incompatible Products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure guidelines** This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

#### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/face Protection** If splashes are likely to occur, wear: Goggles. Eye/face Protection.

**Skin and body protection** Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin wash with soap and water.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	-	<b>Odor</b>	Mild petroleum odor
<b>Appearance</b>	Transparent, yellow tinted fluid	<b>Odor threshold</b>	No information available
<b>Color</b>	light yellow		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point/freezing point</b>	No information available	
<b>Boiling Point/Range</b>	No information available	
<b>Flash point</b>	> 93.3 °C / > 200 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific gravity</b>	0.87-0.89	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>		
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	21.0-47.0 @40C mm <sup>2</sup> /s	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

### Other information

<b>Softening point</b>	No information available
<b>VOC Content</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

None under normal processing.

<b>Hazardous polymerization</b>	Hazardous polymerization does not occur.
---------------------------------	--

### Conditions to avoid

Excessive heat. High energy sources of ignition.

### Incompatible materials

Strong oxidizing agents.

### Hazardous decomposition products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available
<b>Inhalation</b>	Inhalation of vapors in high concentration may cause irritation of respiratory system.
<b>Eye contact</b>	May cause irritation. Avoid contact with eyes.
<b>Skin contact</b>	May cause eye/skin irritation. Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Do NOT taste or swallow.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	> 15 g/kg ( Rat )	-	-
Lubricating oils, petroleum, hydrotreated spent 64742-58-1	> 2000 mg/kg ( Rat )	> 4480 mg/kg ( Rabbit )	-
2-ethylhexyl zinc dithiophosphate 4259-15-8	= 3100 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	-
2,6-di-tert-butylphenol 128-39-2	> 5000 mg/kg ( Rat )	> 10 g/kg ( Rabbit )	-
calcium alkylarylsulphonate 90194-27-7	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	-

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** Mineral oils are known to cause cancer because of carcinogenic components (e.g. benzene). The mineral oil in this product is highly refined and should not be considered a carcinogen. Used lubricating oil may contain hazardous components which have the potential to cause skin cancer. Continuous long-term contact with used lubricating oils has caused skin cancer in animal tests. .

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	-	Group 1	-	X

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration hazard** No information available.

### Numerical measures of toxicity - Product Information

**Unknown Aquatic Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity  
The following values are calculated based on chapter 3.1 of the GHS document .

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Lubricating oils, petroleum, hydrotreated spent 64742-58-1	-	3.2: 96 h Pimephales promelas mg/L LC50 semi-static 79.6: 96 h Brachydanio rerio mg/L LC50 semi-static	-
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
2-ethylhexyl zinc dithiophosphate 4259-15-8	1.0 - 5.0: 96 h Pseudokirchneriella subcapitata mg/L EC50	1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static 10.0 - 35.0: 96 h Pimephales promelas mg/L LC50 semi-static	1 - 1.5: 48 h Daphnia magna mg/L EC50
2,6-di-tert-butylphenol 128-39-2	-	-	0.45: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
2-ethylhexyl zinc dithiophosphate 4259-15-8	2.86

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Waste Disposal Method**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container.

**14. TRANSPORT INFORMATION****DOT**

Not regulated

**IATA**

PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO TI OR IATA DGR

**15. REGULATORY INFORMATION****International Inventories**

TSCA	Does not comply
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply

<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Complies

**Legend:**

All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	No
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	No
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
2-ethylhexyl zinc dithiophosphate 4259-15-8	X	-	X

**U.S. EPA Label Information**

**EPA Pesticide registration number** Not Applicable

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health hazards</b> 0	<b>Flammability</b> 1	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 0	<b>Flammability</b> 1	<b>Physical hazards</b> 0	<b>Personal protection</b> X

**Issuing Date** 15-Feb-2010

Revision Date 03-Mar-2017

**Revision Note**

SDS sections updated 2 11

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**